# Safety Data Sheet



ACRYPOL STREET LINES

Product:

Supersedes: None

Acrypol + All Colours

Version: 1

Page 1 of 8

Date Prepared: February 2015

## SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Acrypol + All Colours

Product Codes: RC3004, RC3005 & RC3006

1.2. Relevant identified uses of the substance or mixture and uses advised against

Uses:

Industrial Waterproof Roof Coating

Not to be used for:

All other uses

1.3. Details of the supplier of the safety data sheet

ACRYPOL PRODUCTS LTD, Unit 4, Asher Court, Lyncastle Way, Barleycastle Lane, Appleton, Warrington,

WA4 4ST, United Kingdom

Tel: +44 (0) 1925 213 655

Fax: +44 (0) 1925 213 656

e-mail Web site info@acrypolproducts.co.uk www.acrypolproducts.co.uk

1.4. Emergency telephone number

+44 (0) 1925 213 655 (09:00 to 17:00 UK time)

#### SECTION 2. HAZARDS IDENTIFICATION

## 2.1. Classification of the substance or mixture

CLP Classification	DPD Classification for information only
Flammable Liquid Cat 3 - H226	Flammable - R10
For full wording of Hazard statements see Section 16	For full wording of Risk phrases see Section 16

#### 2.2. Label elements

Signal Word: WARNING

**Pictograms** 



**H** Statements

H226

Flammable liquid and vapour

Supplemental information

None.

P Statements

P210

Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No Smoking.

P370+P378

In case of fire: Use Foam, CO2, Powder or Water Fog to

extinguish

P403+P233

Store in a well-ventilated place. Keep container tightly closed

2.3. Other hazards

None known





Product:

Supersedes: None

Acrypol + All Colours

Version: 1

Page 2 of 8

Date Prepared: February 2015

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.2. Mixtures

Hazardous component(s)

## Under CLP EC1272/2008

Ingredient	CAS/EC Number	REACH Registration Number	%	CLP Hazard Category	H Statements
2-Methoxy-1- methylethyl acetate *	108-65-6 / 203-603-9	01-2119475791-29	25 - 50	Flammable Liquid 3	H226

<sup>\*</sup> Has WEL - see Section 8

For full wording of H-statements see Section 16.

#### Under DPD EC1999/45

Ingredient	CAS/EC Number	REACH Registration Number	%	Symbol	Risk Phrases
2-Methoxy-1- methylethyl acetate *	108-65-6 / 203-603-9	01-2119475791-29	25 - 50	None	R10

<sup>\*</sup> Has WEL - see Section 8

For full wording of Risk phrases see Section 16.

## **SECTION 4. FIRST-AID MEASURES**

#### 4.1. Description of first aid measures

#### Inhalation

Remove patient to fresh air, allow to rest and keep warm. If symptoms develop, seek medical attention.

## Skin contact

Wash immediately with plenty of soap and water. Do NOT use solvents or thinners. Remove any contaminated clothing and launder before reuse. If symptoms develop, seek medical attention.

## Eye contact

Flush immediately with plenty of water for at least 15 minutes, keeping eyelids open. If symptoms develop, seek medical attention.

## Ingestion

DO NOT induce vomiting! Rinse mouth out with water, but do not give anything to drink. If symptoms develop, seek medical attention.

#### Personal precautions

Ensure that those giving first aid treatment do not get contaminated by product spills, etc. Wear suitable protective clothing, gloves, safety goggles. See also Section 8.

## 4.2. Most important symptoms and effects, both acute and delayed

Repeated or prolonged exposure may cause skin dryness or cracking.

# 4.3. Indication of any immediate medical attention and special treatment needed

None other than above.





**Product:**Supersedes: None

Acrypol + All Colours

Version: 1

Page 3 of 8

Date Prepared: February 2015

#### SECTION 5. FIRE-FIGHTING MEASURES

## 5.1. Extinguishing media

- Suitable:

Water fog, foam, dry powder or carbon dioxide.

Water jet.

- Not to be used:

5.2. Special hazards arising from the substance or mixture

None other than those emitted by materials of construction.

**5.3.** Advice for fire fighters Wear self-contained breathing apparatus and protective clothing. Cool closed containers exposed to fire with water. Prevent fire fighting water entering watercourses or groundwater.

## SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Eliminate all sources of ignition. Wear suitable protective clothing, gloves, safety goggles. See Section 8 for details. Avoid breathing vapours. Turn leaking containers leak-side up to prevent the escape of liquid. Mark out the contaminated area with signs and prevent access to unauthorised personnel.

**6.2. Environmental precautions** Prevent from entering sewers or the immediate environment. Contain the spillage using bunding. In case of large spill, inform local police and/or fire brigade.

## 6.3. Methods and material for containment and cleaning up

- on soil: Absorb onto inert material such as sand or earth. Transfer to a closable, labelled salvage container for disposal as Hazardous Waste. See Section 13.
- on water: Recover by skimming and/or absorption with floating absorbent packs.
- 6.4. Reference to other sections

See Section 8 for details of protective equipment.

See Section 13 for details of disposal.

## SECTION 7. HANDLING AND STORAGE

**7.1. Precautions for safe handling** Ensure there is sufficient ventilation of the area. Do not smoke. Avoid sources of ignition. Avoid contact with skin and eyes. Do not ingest. Avoid breathing vapours. Vapours are heavier than air and may spread along floors and accumulate in pits and hollows.

- **7.2. Conditions for safe storage, including any incompatibilities** Store in a cool, well ventilated area in original containers. Keep container tightly closed when not in use. Follow HSE guidelines for the storage of Flammable Liquids and Packaged Dangerous Substances (HSG51 & HSG71). Keep away from sources of ignition.
- 7.3. Specific end use(s)

Industrial Waterproof Roof Coating.

Product:



Acrypol + All Colours

Supersedes: None Version: 1



Page 4 of 8

Date Prepared: February 2015

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Ingredient	Country	TWA 8hr		STEL 15mins		Notes/Reference
		ppm	mg/m³	ppm	mg/m³	
2-Methoxy-1-methylethyl	UK	50	274	100	548	Sk - EH40
acetate						
Barium sulphate	UK					EH40
total inhalable		-	10	-	(C#)	
respirable		-	4	-		
Amorphous silica	UK					EH40
total inhalable		-	6	-	7-2	
respirable		-	2.4	-	-	
Titanium Dioxide	UK					EH40
total inhalable		-	10	-	-	
respirable		-	4	-	-	
Carbon Black	UK	-	3.5	-	7	EH40
Mica	UK					EH40
total inhalable			10	=	-	
respirable		-	0.8	-	-	

Monitoring procedures

None specified

**Note:** During sanding/cutting processes nuisance dusts may be formed which have Workplace Exposure Levels set as shown below. Wet sanding is recommended.

Ingredient	Country T		A 8hr	STEL 15mins		Reference
		ppm	mg/m³	ppm	mg/m³	
Inhalable dusts	UK	10	•	-	-	EH40/COSHH
Respirable dusts		4			-	

Monitoring procedures

None specified

## 8.2. Exposure Controls

Recommended engineering controls

Ensure good ventilation. Arrange for eye wash possibility.

#### Personal protection

Always check applicability with your supplier of protective equipment.

- **Respiratory protection:** Air-fed or self-contained breathing apparatus if exposure cannot be controlled below the levels shown above during spraying. Particle filtering masks should be worn during sanding if exposure to dusts cannot be avoided by general or local ventilation.
- Skin protection:

Laboratory coat or overalls

Eye protection:

Splash proof safety glasses or goggles.

- Hand protection: Nitrile gloves. (Break-through times can vary depending on thickness, use and source. Change gloves regularly)

## Safety Data Sheet



Product: Acrypol + All Colours Supersedes: None Version: 1

Page 5 of 8

Date Prepared: February 2015

General hygiene: Do not eat, drink, or smoke while using this product. Immediately take off any contaminated clothing and launder before re-use. Wash hands and/or face before breaks and at the end of the shift.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

**Appearance** Liquid, colour varies - can be White, Grey or Black depending

on version (see can)

Odour Ethereal

Odour Threshold Value: Not determined

pH (concentrated product) Not applicable - organic liquid Melting point (°C) Not determined

Boiling point/range (°C) Not determined

Flash point (Pensky Martens) (°C) 32 - 55

Evaporation rate Not determined Flammability Flammable liquid

Explosive properties/limits Not determined Vapour pressure of solvent (kPa at x°C) Not determined

Vapour density Not determined but heavier than air

Density at 20°C (kg/m<sup>3</sup>) 1.12 - 1.14

Solubility in water (% by weight) **Immiscible** 

Solubility in solvents Miscible with most non-polar solvents Partition coefficient of solvent (log Kow) Not determined

Auto-ignition temperature (°C) Not determined Decomposition temperature (°C) Not determined Kinematic Viscosity (cSt @ 40°C) Not determined

Oxidising properties Not considered to be oxidising

#### 9.2. Other information

Note: These are typical values and do not constitute a specification.

## SECTION 10. STABILITY AND REACTIVITY

10.1. Reactivity Stable under normal conditions of use.

10.2. Chemical stability Stable under normal conditions of use.

10.3. Possibility of hazardous reactions None expected.

10.4. Conditions to avoid Sources of ignition.

10.5. Incompatible materials Strong oxidising agents. Strong acids and alkalis.

10.6. Hazardous decomposition products In fire, emits none other than those emitted by materials of construction.



ACRIPOL PRINTER LIMITED

Product:

Supersedes: None

Acrypol + All Colours

Version: 1

Page 6 of 8

Date Prepared: February 2015

## SECTION 11. TOXICOLOGICAL INFORMATION

#### 11.1. Information on toxicological effects

No data available on mixture. Data based on individual components shown below:

(a) Acute toxicity Reason for no classification: Data conclusive but not sufficient for

classification.

(b) Irritation Reason for no classification: Data conclusive but not sufficient for

classification.

(c) Corrosivity Reason for no classification: Data conclusive but not sufficient for

classification.

(d) Sensitisation Reason for no classification: Data conclusive but not sufficient for

classification.

(e) Repeat dose toxicity Reason for no classification: Data conclusive but not sufficient for

classification.

(f) Carcinogenicity Reason for no classification: Data conclusive but not sufficient for

classification.

(g) Mutagenicity Reason for no classification: Data conclusive but not sufficient for

classification.

(h) Toxicity for reproduction Reason for no classification: Data conclusive but not sufficient for

classification.

**Likely routes of exposure:** Inhalation, skin and eye contact.

Symptoms related to the physical, chemical and toxicological characteristics:

Repeated or prolonged exposure may cause skin dryness or cracking.

Delayed and immediate effects as well as chronic effects from short and long-term exposure:

None other than above.

Other information:

None.

#### SECTION 12. ECOLOGICAL INFORMATION

No data available on mixture. No individual components have reported ecological problems

12.1. Toxicity

None by calculation

12.2. Persistence and degradability

Biodegradability:

Not determined

12.3. Bioaccumulative potential

Partition Coefficient:

Not determined

12.4. Mobility in soil

Not determined

12.5. Results of PBT and vPvB assessment

Does not fulfil the criteria for classification as PBT or vPvB.

12.6. Other adverse effects

None known

Product:



Acrypol + All Colours Supersedes: None

Version: 1

Page 7 of 8

Date Prepared: February 2015

This product is not classified as hazardous to the environment under the rules set out in the EU Classification, Labelling and Packaging Regulations EC1272/2008.

## SECTION 13. DISPOSAL CONSIDERATIONS

## 13.1. Waste treatment methods

Dispose of as Hazardous Waste, via a licensed contractor ensuring that all Disposal of product: national and local authority requirements are complied with. It is not suitable for landfill. The preferred method of disposal is by incineration in appropriate equipment.

Disposal of packaging: Contaminated packing should be disposed of as Hazardous Waste, as above, according to local authority guidelines.

## SECTION 14. TRANSPORT INFORMATION

14.1. UN number 1263 14.2. UN proper shipping name Paint 14.3. Transport hazard class(es) 3 14.4. Packing group Ш 14.5. Environmental hazards None

14.6. Special precautions for user See Section 2.2 above

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

#### Modal information:

	Land - ADR	Maritime - IMDG	Air - ICAO/IATA
Transport hazard label	Flammable	Flammable	Flammable
RID/ADR classification	3	3	3
Packaging group	111	111	III
HIN	30	:=:	-
EAC	3Y	·	a.
Tunnel Code	(D/E)	-	~
EmS code(s)	-	FE, SE	-
Marine Pollutant	-	No	-
ERG Code		(=)	3L
Packing Instructions	-	-	Y334, 355, 366 (Passenger & Cargo aircraft)
Max. net qty/package	-	-	60 litres (10 litres non-UN packs) (Passenger aircraft) 220 litres (Cargo aircraft)

## SECTION 15. REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU REACH Regulation 1907/2006 Chemical Agents Directive 98/24/EC UK Control of Substances Hazardous to Health Regulations 2002 SI2677





**Product:**Supersedes: None

Acrypol + All Colours Version: 1 Page 8 of 8

Date Prepared: February 2015

**Note:** The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions, which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

## 15.2. Chemical Safety Assessment

A Chemical Safety Assessment has not been carried out on this mixture.

## **SECTION 16. OTHER INFORMATION**

Inventories

EU All ingredients of this product are listed in EINECS or ELINCS,

unless specifically exempted under EU Directive 67/548/EEC

(as amended).

Sources of data used in this SDS

In-house data files

Literature such as Sax's Dangerous Properties of Industrial Materials, the RSC Dictionary of Substances and their Effects,

**RTECS** 

Suppliers' Safety Data Sheets

In-house test data

CLP Annex VI Tables 3.1 & 3.2

Version number

Date prepared February 2015

Supersedes Version None

Revisions marked with | in the left margin. None

Nature of revision First issue for all colours to REACH format and CLP

classification

Classification carried out under CLP (EC1272/2008) by calculation based on ingredient information.

H-statements used in Sections 2 & 3

H226 Flammable liquid and vapour

R-phrases used in Section 2 & 3 R10 Flammable

Prepared according to precepts of EU Regulation 1907/2006 as amended by Regulation 453/2010

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

End of document

Number of pages = 8