

EVO-STIK GRIPFILL ADHESIVE
Supersedes Date: 11-May-2018Revision Date 18-Mar-2019
Revision Number 1.06**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product Identifier****Product Name** EVO-STIK GRIPFILL ADHESIVE
Pure substance/mixture Mixture**1.2. Relevant identified uses of the substance or mixture and uses advised against****Recommended use** Adhesives.
Uses advised against None known**1.3. Details of the supplier of the safety data sheet****Company Name**Bostik Limited
Common Rd
ST16 3EH
Stafford UK
Tel: +44 (1785) 27 26 25
Fax: +44 (1785) 25 72 36**E-mail address** SDS.box-EU@bostik.com**1.4. Emergency telephone number****United Kingdom** +44 (1785) 272650
Ireland +353 (1) 8624900 (Monday- Friday 9am-5pm)**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture**

Regulation (EC) No 1272/2008

Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2 - (H319)
Chronic aquatic toxicity	Category 3 - (H412)
Flammable liquids	Category 2 - (H225)

2.2. Label Elements**Signal word**
DANGER**Hazard statements**H412 - Harmful to aquatic life with long lasting effects
H319 - Causes serious eye irritation
H315 - Causes skin irritation
H225 - Highly flammable liquid and vapour

Safety Data Sheet

EVO-STIK GRIPFILL ADHESIVE
Supersedes Date: 11-May-2018

Revision Date 18-Mar-2019
Revision Number 1.06

Precautionary statements

P101 - If medical advice is needed, have product container or label at hand
P102 - Keep out of reach of children
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P271 - Use only outdoors or in a well-ventilated area
P280 - Wear protective gloves and eye/face protection
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P312 - Call a POISON CENTER or doctor if you feel unwell
P403 + P233 - Store in a well-ventilated place. Keep container tightly closed
P405 - Store locked up
P501 - Dispose of contents/ container to an approved waste disposal plant

2.3. Other Hazards

In use may form flammable/explosive vapour-air mixture

PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1 Substances

Mixture

3.2 Mixtures

Chemical Name	EC No.	CAS No.	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH Registration Number
Kaolin	310-194-1	1332-58-7	>25 - <40	No data available		Exempt(N)
Styrene-butadiene copolymer	-	9003-55-8	10 - <20	No data available		Exempt(P)
Petroleum resins	265-116-8	64742-16-1	10 - <20	No data available		No data available
Xylenes (o-, m-, p-isomers)	215-535-7	1330-20-7	5 - <10	STOT SE 3 (H335) STOT RE 2 (H373) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Acute Tox. 4 (H312) Acute Tox. 4 (H332) Flam Liq. 3 (H226) Aquatic Chronic 3 (H412)	::	01-2119488216-32-XXXX
Acetone	200-662-2	67-64-1	5 - <10	Eye Irrit. 2 (H319) (EUH066) STOT SE 3		01-2119471330-49-XXXX

Safety Data Sheet

EVO-STIK GRIPFILL ADHESIVE
Supersedes Date: 11-May-2018

Revision Date 18-Mar-2019
Revision Number 1.06

				(H336) Flam. Liq. 2 (H225)		
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	--	5 - <10	STOT SE 3 (H336) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) Aquatic Chronic 2 (H411) Flam. Liq. 2 (H225)		01-2119475515- 33-xxxx
Hydrocarbons, C6, isoalkanes, <5% n-hexane	931-254-9	--	1 - <5	STOT SE 3 (H336) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) Aquatic Chronic 2 (H411) Flam Liq. 2 (H225) (EUH066)		01-2119484651- 34-XXXX
Carbonic acid, calcium salt (1:1)	207-439-9	471-34-1	1 - <3	No data available		01-2119486795- 18-XXXX
Man-made vitreous fibres	926-099-9	--	1 - <3	No data available		01-2119472313- 44-XXXX
Ethylbenzene	202-849-4	100-41-4	1- <2.5	STOT RE 2 (H373) Asp. Tox. 1 (H304) Acute Tox. 4 (H332) Flam Liq. 2 (H225) Aquatic Chronic 3 (H412)		01-2119489370- 35-XXXX
Dusting agent	-	UNKNOWN	0.1 - <1	No data available		No data available
Benzenepropanoic acid, 3,5-bis(1,1-dimethylethyl)-4-hydroxy-, 2,2-bis[[3-[3,5-bis(1,1-di methylethyl)-4-hydroxyp henyl]-1-oxopropoxy]met hyl]-1,3-propanediyl ester	229-722-6	6683-19-8	0.1 - <1	No data available		01-2119491301- 46-XXXX
Titanium dioxide	236-675-5	13463-67-7	0.01 - <0.1	No data available		01-2119489379- 17-XXXX
Quartz (fine fraction)	238-878-4	14808-60-7	0.01 - <0.05	STOT RE 1 (H372)		Exempt
Toluene	203-625-9	108-88-3	0.01 - <0.05	Skin Irrit. 2 (H315) Repr. 2 (H361d) STOT SE 3 (H336) STOT RE 2 (H373) Asp. Tox. 1 (H304)		01-2119471310- 51-XXXX

Safety Data Sheet

EVO-STIK GRIPFILL ADHESIVE
 Supersedes Date: 11-May-2018

Revision Date 18-Mar-2019
 Revision Number 1.06

				Flam. Liq. 2 (H225)		
Hexane	203-777-6	110-54-3	<0.0015	Skin Irrit. 2 (H315) Repr. 2 (H361f) STOT SE 3 (H336) STOT RE 2 (H373) Asp. Tox. 1 (H304) Aquatic Chronic 2 (H411) Flam. Liq. 2 (H225)	STOT RE 2 :: C>=5%	01-2119480412-44-XXXX
Cyclohexane	203-806-2	110-82-7	<0.0015	Skin Irrit. 2 (H315) STOT SE 3 (H336) Asp. Tox. 1 (H304) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410) Flam. Liq. 2 (H225)		01-2119463273-41-XXXX

Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	Take a copy of the Safety Data Sheet when going for medical treatment.
Inhalation	Remove to fresh air. IF exposed or concerned: Get medical advice/attention.
Eye contact	Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a doctor.
Skin contact	Wash skin with soap and water. In the case of skin irritation or allergic reactions see a doctor.
Ingestion	Clean mouth with water. Do NOT induce vomiting. Drink 1 or 2 glasses of water. Never give anything by mouth to an unconscious person.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors Treat symptomatically.

Safety Data Sheet

EVO-STIK GRIPFILL ADHESIVE
Supercedes Date: 11-May-2018

Revision Date 18-Mar-2019
Revision Number 1.06

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media Full water jet. Do not scatter spilled material with high pressure water streams.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical Thermal decomposition can lead to release of toxic and corrosive gases/vapours.

5.3. Advice for firefighters

Special protective equipment for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation. Avoid contact with skin, eyes or clothing.

Other information Ventilate the area. Prevent further leakage or spillage if safe to do so.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Do not flush into surface water or sanitary sewer system. Do not allow to enter into soil/subsoil. See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for containment Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Ensure adequate ventilation. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Take off all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep container tightly closed in a dry and well-ventilated place. Keep away from food, drink and animal feedingstuffs.

7.3. Specific end use(s)

Safety Data Sheet

EVO-STIK GRIPFILL ADHESIVE
 Supersedes Date: 11-May-2018

Revision Date 18-Mar-2019
 Revision Number 1.06

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Exposure Limits This product, as supplied, does not contain any hazardous materials with occupational exposure limits established by the region specific regulatory bodies

Chemical Name	European Union	Ireland	United Kingdom
Kaolin 1332-58-7	-	TWA: 2 mg/m ³	TWA: 2 mg/m ³ STEL: 6 mg/m ³
Xylenes (o-, m-, p- isomers) 1330-20-7	TWA: 50 ppm TWA: 221 mg/m ³ STEL: 100 ppm STEL: 442 mg/m ³ *	TWA: 50 ppm TWA: 221 mg/m ³ STEL: 100 ppm STEL: 442 mg/m ³ Sk*	TWA: 50 ppm TWA: 220 mg/m ³ STEL: 100 ppm STEL: 441 mg/m ³ Sk*
Acetone 67-64-1	TWA: 500 ppm TWA: 1210 mg/m ³	TWA: 500 ppm TWA: 1210 mg/m ³ STEL: 1500 ppm STEL: 3630 mg/m ³	TWA: 500 ppm TWA: 1210 mg/m ³ STEL: 1500 ppm STEL: 3620 mg/m ³
Ethylbenzene 100-41-4	TWA: 100 ppm TWA: 442 mg/m ³ STEL: 200 ppm STEL: 884 mg/m ³ *	TWA: 100 ppm TWA: 442 mg/m ³ STEL: 200 ppm STEL: 884 mg/m ³ Sk*	TWA: 100 ppm TWA: 441 mg/m ³ STEL: 125 ppm STEL: 552 mg/m ³ Sk*
Hexane 110-54-3	TWA: 20 ppm TWA: 72 mg/m ³	TWA: 20 ppm TWA: 72 mg/m ³ STEL: 60 ppm STEL: 216 mg/m ³ Sk*	TWA: 20 ppm TWA: 72 mg/m ³ STEL: 60 ppm STEL: 216 mg/m ³
Cyclohexane 110-82-7	TWA: 200 ppm TWA: 700 mg/m ³	TWA: 200 ppm TWA: 700 mg/m ³ STEL: 600 ppm STEL: 2100 mg/m ³	TWA: 100 ppm TWA: 350 mg/m ³ STEL: 300 ppm STEL: 1050 mg/m ³

Chemical Name	European Union	Ireland	United Kingdom
Xylenes (o-, m-, p- isomers) 1330-20-7	-	-	650 mmol/mol creatinine urine

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)

Xylenes (o-, m-, p- isomers) (1330-20-7)

Type Long term Systemic health effects Worker
 Exposure route Dermal
 Derived No Effect Level (DNEL) 180 mg/kg bw/d

Type Long term Systemic health effects Worker
 Exposure route Inhalation
 Derived No Effect Level (DNEL) 77 mg/m³

Type Short term Local health effects Systemic health effects Worker
 Exposure route Inhalation
 Derived No Effect Level (DNEL) 289 mg/m³

Acetone (67-64-1)

Type Long term Systemic health effects Worker
 Exposure route Dermal
 Derived No Effect Level (DNEL) 186 mg/kg bw/d

Safety Data Sheet

EVO-STIK GRIPFILL ADHESIVE
Supersedes Date: 11-May-2018

Revision Date 18-Mar-2019
Revision Number 1.06

Type	Short term Local health effects Worker
Exposure route	Inhalation
Derived No Effect Level (DNEL)	2420 mg/m ³

Type	Long term Systemic health effects Worker
Exposure route	Inhalation
Derived No Effect Level (DNEL)	1210 mg/m ³

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (--)

Type	Worker Long term Systemic health effects
Exposure route	Inhalation
Derived No Effect Level (DNEL)	2085 mg/m ³

Type	Worker Long term Systemic health effects
Exposure route	Dermal
Derived No Effect Level (DNEL)	300 mg/kg bw/d

Titanium dioxide (13463-67-7)

Type	Worker Long term Local health effects
Exposure route	Inhalation
Derived No Effect Level (DNEL)	10 mg/m ³

Toluene (108-88-3)

Type	Long term Systemic health effects Worker
Exposure route	Dermal
Derived No Effect Level (DNEL)	384 mg/kg bw/d

Type	Long term Systemic health effects Local health effects Worker
Exposure route	Inhalation
Derived No Effect Level (DNEL)	192 mg/m ³

Type	Short term Local health effects Systemic health effects Worker
Exposure route	Inhalation
Derived No Effect Level (DNEL)	384 mg/m ³

Derived No Effect Level (DNEL)

Acetone (67-64-1)

Type	Consumer Long term Systemic health effects
Exposure route	Inhalation
Derived No Effect Level (DNEL)	200 mg/m ³

Type	Consumer Long term Systemic health effects
Exposure route	Dermal
Derived No Effect Level (DNEL)	62 mg/kg bw/d

Type	Consumer Long term Systemic health effects
Exposure route	Oral
Derived No Effect Level (DNEL)	62 mg/kg bw/d

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (--)

Type	Consumer Long term Systemic health effects
Exposure route	Inhalation
Derived No Effect Level (DNEL)	447 mg/m ³

Type	Consumer Long term Systemic health effects
Exposure route	Dermal
Derived No Effect Level (DNEL)	149 mg/kg bw/d

Safety Data Sheet

EVO-STIK GRIPFILL ADHESIVE
Supersedes Date: 11-May-2018

Revision Date 18-Mar-2019
Revision Number 1.06

Type	Consumer Long term Systemic health effects
Exposure route	Oral
Derived No Effect Level (DNEL)	149 mg/kg bw/d

Titanium dioxide (13463-67-7)	
Type	Consumer Long term Systemic health effects
Exposure route	Oral
Derived No Effect Level (DNEL)	700 mg/kg bw/d

Predicted No Effect Concentration (PNEC) No information available.

Predicted No Effect Concentration (PNEC)	
Acetone (67-64-1)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	10.6 mg/l
Freshwater - intermittent	21 mg/l
Marine water	1.06 mg/l
Microorganisms in sewage treatment	100 mg/l
Freshwater sediment	30.4 mg/kg dry weight
Marine water	3.04 mg/kg dry weight
Soil	29.5 mg/kg dry weight

Titanium dioxide (13463-67-7)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Marine water	0.0184 mg/l
Freshwater sediment	1000 mg/kg
Freshwater	0.184 mg/l
Marine sediment	100 mg/kg
Soil	100 mg/kg
Microorganisms in sewage treatment	100 mg/l
Freshwater - intermittent	0.193 mg/l

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/face protection Tight sealing safety goggles. Face protection shield.
Hand protection Wear protective gloves. The breakthrough time of the gloves depends on the material and the thickness as well as the temperature.
Skin and body protection Antistatic footwear. Wear fire/flame resistant/retardant clothing. Suitable protective clothing.
Respiratory protection In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit. In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls Do not allow into any sewer, on the ground or into any body of water.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical State Liquid
Appearance Liquid
Colour No information available
Odour Solvent
Odour Threshold No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No data available	
Melting point / freezing point	No data available	
Boiling point / boiling range	= 60 °C	

Safety Data Sheet

EVO-STIK GRIPFILL ADHESIVE
Supersedes Date: 11-May-2018

Revision Date 18-Mar-2019
Revision Number 1.06

Flash Point	-10 °C	
Evaporation Rate	No data available	
Flammability (solid, gas)	No data available	
Flammability Limit in Air		
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapour Pressure	No data available	
Vapour Density	No data available	
Relative Density	No data available	
Water Solubility	No data available	
Solubility(ies)	No data available	
Partition coefficient	No data available	
Autoignition Temperature	No data available	
Decomposition Temperature	No data available	
Kinematic Viscosity	500 mm ² /s	@ 40°C
Dynamic Viscosity	No data available	
Explosive properties	No data available	
Oxidising properties	No data available	

9.2. Other information

Solid content (%)	No information available
Softening Point	No information available
Molecular Weight	No information available
VOC (volatile organic compound)	approx. 370 g/L
Density	1.18
Bulk Density	No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion Data

Sensitivity to mechanical impact None.

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid None known based on information supplied.

10.5. Incompatible materials

Incompatible materials None known based on information supplied.

10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions. Stable under recommended storage conditions.

Safety Data Sheet

EVO-STIK GRIPFILL ADHESIVE
 Supersedes Date: 11-May-2018

Revision Date 18-Mar-2019
 Revision Number 1.06

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Information on likely routes of exposure

Product information

Inhalation	Based on available data, the classification criteria are not met.
Eye contact	Based on available data, the classification criteria are not met.
Skin contact	Based on available data, the classification criteria are not met.
Ingestion	Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Numerical measures of toxicity

No information available

Acute Toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (dermal)	6,830.00 mg/kg
ATEmix (inhalation-dust/mist)	40.00 mg/l

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Kaolin 1332-58-7	LD50 (rat) > 2000 mg/kg	> 5000 mg/kg (Rat)	1.5 mg/l 4hr
Styrene-butadiene copolymer 9003-55-8		LD50 >2000 mg/Kg	
Petroleum resins 64742-16-1	>5000 mg/Kg (rat)	>2000 mg/Kg (rabbit)	
Xylenes (o-, m-, p- isomers) 1330-20-7	= 3500 mg/kg (Rat)	> 1700 mg/kg (Rabbit) > 4350 mg/kg (Rabbit)	= >47635 mg/L (Rat) 4 h = >5000 ppm (Rat) 4 h
Acetone 67-64-1	= 5800 mg/kg (Rat)	>15800 mg/Kg (rat)	= 79 mg/l(Rat) 4 h
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics --	LD50 >5840 mg/kg Rat	LD50 >2920 mg/kg (Rat)	LC50 >23.3 mg/L (4h)(Rat, vapour) (OECD 403)
Hydrocarbons, C6, isoalkanes, <5% n-hexane --	>16750 mg/Kg (rat)	>3350 mg/Kg (rabbit OECD 402)	259354 mg/m ³ (vapour) (rat OECD 403)
Carbonic acid, calcium salt (1:1) 471-34-1	LD50 > 2000 mg/kg (Rat) OECD 420	LD50 >2000 mg/kg (Rat) OECD 402	LC50 (4h) >3mg/ml (Rat)
Ethylbenzene 100-41-4	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 1432 mg/L (Rat) 4 h
Benzenepropanoic acid, 3,5-bis(1,1-dimethylethyl)-4-hy droxy-, 2,2-bis[[3-[3,5-bis(1,1-dimethyl ethyl)-4-hydroxyphenyl]-1-oxop ropoxy]methyl]-1,3-propanediyl ester	>5000 mg/Kg (Rat) OECD 401	>3160 mg/Kg (Rabbit)	> 46 mg/L (Rat) 1 h

Safety Data Sheet

EVO-STIK GRIPFILL ADHESIVE
Supersedes Date: 11-May-2018

Revision Date 18-Mar-2019
Revision Number 1.06

6683-19-8			
Titanium dioxide 13463-67-7	> 10000 mg/kg (Rat)		
Quartz (fine fraction) 14808-60-7	>2000 mg/kg (Rat)		
Toluene 108-88-3	= 5580 mg/kg (Rat)	= 12000 mg/kg (Rabbit)	> 20 mg/L (Rat) 4 h
Hexane 110-54-3	= 25 g/kg (Rat)	= 3000 mg/kg (Rabbit)	= 48000 ppm (Rat) 4 h
Cyclohexane 110-82-7	= 12705 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 9500 ppm (Rat) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

Chemical Name	European Union
Toluene 108-88-3	Repr. 2
Hexane 110-54-3	Repr. 2

Component Information		
Toluene (108-88-3)		
Method	Species	Results
OECD 407	in vivo	reproductive toxicant

STOT - single exposure Based on available data, the classification criteria are not met.

STOT - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity Not considered to be harmful to aquatic life.

Chemical Name	Algae/aquatic plants	Fish	Toxicity to Micro-organisms	Crustacea	M-Factor
Kaolin 1332-58-7	IC 50 (72h) > 1000 mg/l	LC 50 (96h) > 1000 mg/l	-	EC 50 (48h) > 1000 mg/l (Daphnia magna)	-
Xylenes (o-, m-, p-)	-	LC50 96 h 2.6	EC50 = 0.0084	EC50 48 h = 3.4	-

Safety Data Sheet

EVO-STIK GRIPFILL ADHESIVE
Supersedes Date: 11-May-2018

Revision Date 18-Mar-2019
Revision Number 1.06

isomers) 1330-20-7		mg/L (Oncorhynchus mykiss) (OECD 203)	mg/L 24 h	mg/L (water flea)	
Acetone 67-64-1	-	LC50 96 h 4.74 - 6.33 mL/L (Oncorhynchus mykiss)	EC50 = 14500 mg/L 15 min	EC50 48 h 10294 - 17704 mg/L (Daphnia magna Static)	-
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics --	-	-	-	EL50 (48h) =3mg/L Daphnia	-
Hydrocarbons, C6, isoalkanes, <5% n-hexane --	13.6 mg/l (Pseudokirchneriella subcapitata)	18.3 mg/l (Oncorhynchus mykiss)	-	31.9 mg/l (Daphnia magna)	-
Carbonic acid, calcium salt (1:1) 471-34-1	IC50 72H Algae >1000 mg/l	CL50 96H Fish >1000 mg/l	-	EC50 48H Daphnia >1000 mg/l	-
Ethylbenzene 100-41-4	EC50 72 h 2.6 - 11.3 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h = 4.2 mg/L (Oncorhynchus mykiss semi-static)	EC50 = 9.68 mg/L 30 min EC50 = 96 mg/L 24 h	EC50: 1.8 - 2.4mg/L (48h, Daphnia magna)	-
Benzenepropanoic acid, 3,5-bis(1,1-dimethylethyl)-4-hydroxy-, 2,2-bis[[3-[3,5-bis(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]methyl]-1,3-propanediyl ester 6683-19-8	EC50: >100mg/L (72h, Desmodesmus subspicatus)	LC50 96 h > 100 mg/L (Brachydanio rerio) OECD 203	-	EC50 24 h > 86 mg/L (Daphnia magna) OECD 202	-
Toluene 108-88-3	EC50 72 h = 12.5 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h 5.89 - 7.81 mg/L (Oncorhynchus mykiss flow-through) LC50 96 h = 5.8 mg/L (Oncorhynchus mykiss semi-static)	EC50 = 19.7 mg/L 30 min	EC50: =11.5mg/L (48h, Daphnia magna) EC50: 5.46 - 9.83mg/L (48h, Daphnia magna)	-
Hexane 110-54-3	-	LC50: 2.1 - 2.98mg/L (96h, Pimephales promelas)	-	EC50: >1000mg/L (24h, Daphnia magna)	-
Cyclohexane 110-82-7	EC50 72 h > 9.3 mg/L (Pseudokirchneriella subcapitata)	LC50: 3.96 - 5.18mg/L (96h, Pimephales promelas) LC50: 24.99 - 44.69mg/L (96h, Lepomis macrochirus) LC50: 23.03 - 42.07mg/L (96h, Pimephales promelas) LC50: 48.87 - 68.76mg/L (96h, Poecilia reticulata)	EC50 = 85.5 mg/L 5 min EC50 = 93 mg/L 10 min	EC50: >400mg/L (24h, Daphnia magna)	-

12.2. Persistence and degradability

Persistence and degradability No information available.

Safety Data Sheet

EVO-STIK GRIPFILL ADHESIVE
 Supersedes Date: 11-May-2018

Revision Date 18-Mar-2019
 Revision Number 1.06

Component Information			
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (--)			
Method	Exposure time	Value	Results
OECD Test No. 301F: Ready Biodegradability: Manometric Respirometry Test (TG 301 F)	28 days	83%	Readily biodegradable

12.3. Bioaccumulative potential

Bioaccumulative potential No information available.

Chemical Name	Partition coefficient	Bioconcentration factor (BCF)
Xylenes (o-, m-, p- isomers) 1330-20-7	3.15	15
Acetone 67-64-1	-0.24	0.69
Hydrocarbons, C6, isoalkanes, <5% n-hexane --	3.6	501
Ethylbenzene 100-41-4	3.2	15
Benzenepropanoic acid, 3,5-bis(1,1-dimethylethyl)-4-hydroxy-, 2,2-bis[[3-[3,5-bis(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]methyl]-1,3-propanediyl ester 6683-19-8	22.7	2.3
Toluene 108-88-3	2.7	-
Cyclohexane 110-82-7	3.44	167

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment No information available.

Chemical Name	PBT and vPvB assessment
Xylenes (o-, m-, p- isomers) 1330-20-7	The substance is not PBT / vPvB
Acetone 67-64-1	The substance is not PBT / vPvB
Carbonic acid, calcium salt (1:1) 471-34-1	The substance is not PBT / vPvB PBT assessment does not apply
Ethylbenzene 100-41-4	The substance is not PBT / vPvB
Benzenepropanoic acid, 3,5-bis(1,1-dimethylethyl)-4-hydroxy-, 2,2-bis[[3-[3,5-bis(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]methyl]-1,3-propanediyl ester 6683-19-8	The substance is not PBT / vPvB
Titanium dioxide 13463-67-7	The substance is not PBT / vPvB PBT assessment does not apply
Toluene 108-88-3	The substance is not PBT / vPvB PBT assessment does not apply
Hexane	The substance is not PBT / vPvB

Safety Data Sheet

EVO-STIK GRIPFILL ADHESIVE
Supersedes Date: 11-May-2018

Revision Date 18-Mar-2019
Revision Number 1.06

110-54-3	
Cyclohexane	The substance is not PBT / vPvB
110-82-7	

12.6. Other adverse effects

Other Adverse Effects No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products	Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.
Contaminated packaging	Do not reuse empty containers. Handle contaminated packages in the same way as the product itself.
European Waste Catalogue	08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances
Other information	Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Note: The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments made in non-bulk packages (see regulatory definition). The information shown here, may not always agree with the bill of lading shipping description for the material.

Land transport (ADR/RID)

14.1 UN Number	UN1133
14.2 Proper Shipping Name	Adhesives
14.3 Transport hazard class(es)	3
Labels	3
14.4 Packing Group	III
Description	UN1133, Adhesives, 3, III, (D/E)
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	None
Classification Code	F1
Tunnel restriction code	(D/E)
Limited Quantity (LQ)	5 L
ADR Hazard Id (Kemmler Number)	30

IMDG

14.1 UN Number	UN1133
14.2 Proper Shipping Name	Adhesives
14.3 Transport hazard class(es)	3
14.4 Packing Group	III
Description	UN1133, Adhesives, 3, III, (-10°C c.c.)
14.5 Marine Pollutant	Np
14.6 Special Provisions	223, 955
Limited Quantity (LQ)	5 L
EmS-No.	F-E, S-D
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	No information available

Air transport (ICAO-TI / IATA-DGR)

14.1 UN Number	UN1133
----------------	--------

Safety Data Sheet

EVO-STIK GRIPFILL ADHESIVE
Supersedes Date: 11-May-2018

Revision Date 18-Mar-2019
Revision Number 1.06

14.2 Proper Shipping Name	Adhesives
14.3 Transport hazard class(es)	3
14.4 Packing Group	III
Description	UN1133, Adhesives, 3, III
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	A3
Limited Quantity (LQ)	10 L
ERG Code	3L

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical Name	CAS No.	Restricted substance per REACH Annex XVII
Kaolin	1332-58-7	
Styrene-butadiene copolymer	9003-55-8	
Petroleum resins	64742-16-1	
Xylenes (o-, m-, p- isomers)	1330-20-7	
Acetone	67-64-1	
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	--	
Hydrocarbons, C6, isoalkanes, <5% n-hexane	--	
Carbonic acid, calcium salt (1:1)	471-34-1	
Man-made vitreous fibres	--	
Ethylbenzene	100-41-4	
Dusting agent	UNKNOWN	
Benzenepropanoic acid, 3,5-bis(1,1-dimethylethyl)-4-hydroxy-, 2,2-bis[[3-[3,5-bis(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]methyl]-1,3-propanediyl ester	6683-19-8	
Titanium dioxide	13463-67-7	
Quartz (fine fraction)	14808-60-7	
Toluene	108-88-3	48.
Hexane	110-54-3	
Cyclohexane	110-82-7	57.

If supplied in neoprene contact adhesives to general public above 0.1% CAS 110-82-7 must be labeled as per restriction.

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Safety Data Sheet

EVO-STIK GRIPFILL ADHESIVE
Supersedes Date: 11-May-2018

Revision Date 18-Mar-2019
Revision Number 1.06

Chemical Name	CAS No.
Kaolin	1332-58-7
Styrene-butadiene copolymer	9003-55-8
Petroleum resins	64742-16-1
Xylenes (o-, m-, p- isomers)	1330-20-7
Acetone	67-64-1
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	--
Hydrocarbons, C6, isoalkanes, <5% n-hexane	--
Carbonic acid, calcium salt (1:1)	471-34-1
Man-made vitreous fibres	--
Ethylbenzene	100-41-4
Dusting agent	UNKNOWN
Benzenepropanoic acid, 3,5-bis(1,1-dimethylethyl)-4-hydroxy-, 2,2-bis[[3-[3,5-bis(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]methyl]-1,3-propanediyl ester	6683-19-8
Titanium dioxide	13463-67-7
Quartz (fine fraction)	14808-60-7
Toluene	108-88-3
Hexane	110-54-3
Cyclohexane	110-82-7

Dangerous substance category per Seveso Directive (2012/18/EU)

P5a - FLAMMABLE LIQUIDS
or
P5b - FLAMMABLE LIQUIDS
or
P5c - FLAMMABLE LIQUIDS

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H373 - May cause damage to organs through prolonged or repeated exposure

H304 - May be fatal if swallowed and enters airways

H332 - Harmful if inhaled

H225 - Highly flammable liquid and vapour

H412 - Harmful to aquatic life with long lasting effects

H315 - Causes skin irritation

H361f - Suspected of damaging fertility

H336 - May cause drowsiness or dizziness

H411 - Toxic to aquatic life with long lasting effects

H400 - Very toxic to aquatic life

H410 - Very toxic to aquatic life with long lasting effects

H335 - May cause respiratory irritation

H319 - Causes serious eye irritation

H312 - Harmful in contact with skin

H226 - Flammable liquid and vapour

Safety Data Sheet

EVO-STIK GRIPFILL ADHESIVE
Supersedes Date: 11-May-2018

Revision Date 18-Mar-2019
Revision Number 1.06

EUH066 - Repeated exposure may cause skin dryness or cracking

Legend

SVHC: Substances of Very High Concern for Authorisation:

Legend SECTION 8: Exposure controls/personal protection

TWA TWA (time-weighted average)

STEL

STEL (Short Term Exposure Limit)

Ceiling Maximum limit value

*

Skin designation

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals

STOT RE Specific target organ toxicity - Repeated exposure

STOT SE Specific target organ toxicity - Single exposure

EWC: European Waste Catalogue

Key literature references and sources for data

Classification and labeling data calculated from data received from raw material suppliers

Prepared By Product Safety & Regulatory Affairs

Revision Date 18-Mar-2019

Indication of changes

Revision note SDS sections updated: 3.

Training Advice Provide adequate information, instruction, and training for operator

Further information No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet